

N-Access 10 Pro







RFID



Password



USB




Access Control

Fingerprint Access Control System

Storage Capacity

Finger Capacity	3000
Card Capacity	1000
Max User	1000
Password	1000
Log Capacity	1,00,000



Features

High-Speed and Accurate Fingerprint Identification
Fingerprint, Card, Password authentication

Output relay for door open.

Supremely low Electric energy consumption.

Highly reliable and durable.

N-Access 10 Pro

Communication Interface

Biometric

FAR	0.0001%
FRR	0.01%
CPU	High speed industrial grade CPU
Verification time	<=0.5 second
RF card options	Proximity



Accepts moist and rough Finger



Accepts Color & Mahendi Finger



USB



Unaffected by High Temperatures $0^{\circ} \sim 45^{\circ}$

Audio/Visual

Display	2.4" TFT Color LCD Screen
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

Access control

Wiegand	Output
Relay	Yes
Support	Push Button, No Touch, Remote, Alarm



Time Attendance



Access Control



SSR Report (Self-Service-Recorder)

Power & Environment

Operating Temperature	0°c ~ 45°c
Power	12V DC / 2A
Dimension	100.24 x 105.2 x 29.4 mm

Disclaimer: Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Connect with us on







BioMax Security









