

# N-BM70W Pro Ultimate Multi Bio







Finger













Face

RFID

Inbuilt Battery

WiFi

LAN

USB

Access Control

## Multi-Bio Attendance and Access Control System

## Storage Capacity

| Face Capacity   | 1200 (1: N) |
|-----------------|-------------|
| Finger Capacity | 5000        |
| Card User       | 1200        |
| Max User        | 1200        |
| Log Capacity    | 1,50,000    |

#### **Fetures**

High-Speed and Accurate Face Identification

Good adaptation for dry, moist and rough fingerprints.


Output relay for door open.

Face, Fingerprint, Card, Password authentication

Supremely low Electric energy consumption.

Highly reliable and durable.

Comprehensive SDK is available for development and integration.



## N-BM70W Pro

#### Communication Interface

| Communication | Wi-Fi, TCP/IP, USB Host |
|---------------|-------------------------|
|---------------|-------------------------|

#### **Biometric**

| Push Data         | YES                        |
|-------------------|----------------------------|
| Sensor type       | 500 DPI                    |
| FAR               | 0.00001%                   |
| FRR               | 0.001%                     |
| OS                | Linux                      |
| Verification time | <1 second                  |
| RF card options   | 125kHz EM (Standard) /     |
|                   | 13.56MHz Mifare (Optional) |

## Audio/Visual


| LCD                      | 2.8" TFT color screen                 |
|--------------------------|---------------------------------------|
| LED Indicator            | Green/Red                             |
| LED for day night vision | Array LED                             |
| Voice instruction        | 16-bit Hi-Fi voice & sound indication |
| Language                 | English                               |

#### Access control

| Relay               | YES                           |
|---------------------|-------------------------------|
| Support Exit Reader | Remote, Push Button, No Touch |

### Power & Environment


| Inbuilt Battery Backup | YES (BIS standard)     |
|------------------------|------------------------|
| Power                  | 12V 2Am (BIS standard) |
| Operating Temperature  | 0°c ~ 50°c             |
| Operating Humidity     | 20% - 80%              |
| Dimension              | 160 x 150 x 65 mm      |



Software

Desktop, Web, Cloud

Accepts Color Finger




**Disclaimer**: Brief specifications are mentioned here, specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Connect with us on







(in) BioMax Access Control